V-Belts RAW EDGE COGGED for industrial use are engergy saving, higher performance belts thanks to their flexibility. Belts with a higher performance level have a longer service life.
Belts with raw edge allow higher slipping resistance even when they are working with low installation tension.

Maximum resistance to heat and oils. High antistatic properties conforming to ISO1813.

Part numbers are identified by two letters (e.g. AX) the belt cross section, and a two or three digit number (e.g. 50) which represents the belt length in inches.

Part No	Outside Length (mm)	Pitch Length (mm)	Inside Length (mm)	Inside Length (inch)
BX24	680	650	610	24
BX26	730	700	660	26
BX28	781	751	711	28
BX30	832	802	762	30
BX31	857	827	787	31
BX32	883	853	813	32
BX33	908	878	838	33
BX34	934	904	864	34
BX35	959	929	889	35
BX36	984	954	914	36
BX37	1010	980	940	37
BX38	1035	1005	965	38
BX39	1061	1031	991	39
BX40	1086	1056	1016	40
BX41	1111	1081	1041	41
BX42	1137	1107	1067	42
BX43	1162	1132	1092	43
BX44	1188	1158	1118	44
BX45	1213	1183	1143	45
BX46	1238	1208	1168	46
BX47	1264	1234	1194	47
BX48	1289	1259	1219	48
BX49	1315	1285	1245	49
BX50	1340	1310	1270	50
BX51	1365	1335	1295	51
BX52	1391	1361	1321	52
BX53	1416	1386	1346	53
BX54	1442	1412	1372	54
BX55	1467	1437	1397	55
BX56	1492	1462	1422	56
BX57	1518	1488	1448	57
BX58	1543	1513	1473	58
BX59	1569	1539	1499	59
BX60	1594	1564	1524	60

Part No	Outside Length (mm)	Pitch Length (mm)	Inside Length (mm)	Inside Length (inch)
BX61	1619	1589	1549	61
BX62	1645	1615	1575	62
BX63	1670	1640	1600	63
BX64	1696	1666	1626	64
BX65	1721	1691	1651	65
BX66	1746	1706	1676	66
BX67	1772	1742	1702	67
BX68	1797	1767	1727	68
BX69	1823	1793	1753	69
BX70	1848	1818	1778	70
BX71	1873	1843	1803	71
BX72	1899	1869	1829	72
BX73	1924	1894	1854	73
BX74	1950	1920	1880	74
BX75	1975	1945	1905	75
BX76	2000	1970	1930	76
BX77	2026	1996	1956	77
BX78	2051	2021	1981	78
BX79	2077	2047	2007	79
BX80	2102	2072	2032	80
BX81	2127	2097	2057	81
BX82	2153	2123	2083	82
BX83	2178	2148	2108	83
BX84	2204	2174	2134	84
BX85	2229	2199	2159	85
BX86	2254	2224	2184	86
BX87	2280	2250	2210	87
BX88	2305	2275	2235	88
B89	2331	2301	2261	89
BX90	2356	2326	2286	90
BX91	2381	2351	2311	91
BX92	2407	2377	2337	92
BX93	2432	2402	2362	93
BX94	2458	2428	2388	94

Part No	Outside Length (mm)	Pitch Length (mm)	Inside Length (mm)	Inside Length (inch)
BX95	2483	2453	2413	95
BX96	2508	2478	2438	96
BX97	2534	2504	2464	97
BX98	2559	2529	2489	98
BX99	2585	2555	2515	99
BX100	2610	2580	2540	100
BX103	2686	2656	2616	103
BX105	2737	2707	2667	105
BX106	2762	2732	2692	106
BX108	2813	2783	2743	108
BX112	2915	2885	2845	112
BX113	2940	2910	2870	113
BX115	2991	2961	2921	115
BX116	3016	2986	2946	116
BX120	3118	3088	3048	120
BX123	3194	3164	3124	123
BX124	3220	3190	3150	124
BX126	3270	3240	3200	126
BX128	3321	3291	3251	128
BX133	3448	3418	3378	133
BX136	3524	3494	3454	136
BX140	3626	3596	3556	140
BX144	3728	3698	3658	144
BX148	3829	3799	3759	148
BX150	3880	3850	3810	150
BX154	3982	3952	3912	154
BX158	4083	4053	4013	158
BX162	4185	4155	4115	162
BX173	4464	4434	4394	173
BX180	4642	4612	4572	180
BX191	4921	4891	4851	191
BX195	5023	4993	4953	195